



WebID definition hash

The questionnaire is not yet open. No one will be able to post an answer until it opens.

Only people identified as participants of the WebID Community Group can answer this form.

The [results of this questionnaire](#) are available only to the participants of the group (and the W3C Team) In addition, answers are sent to the following email address: public-webid@w3.org

You may [designate](#) someone else in your organization to respond to this questionnaire for you.

If you cannot use this on-line questionnaire, you may send your answers by email to public-webid@w3.org using the [text version of this questionnaire](#).

Questionnaire

You're identified as Henry Story, representing The Apache Software Foundation.



What is a WebID?

Given that WebID's must refer to Agents, and that the WebID must be associated with a profile document, (that returns a default representation) the question here is which of the following restrictions one should have for WebIDs.

Note that a URI is defined by [RFC3986](#) and is constructed as follows:

```
foo://example.com:8042/over/there?name=ferret#nose
  \_/\  \_____/ \_____/ \_____/ \_____/
  |   |   |   |   |
scheme authority path query fragment
```

Please look at the detailed arguments for each position [on the wiki before selecting your preferences](#).

Please select the rank-order (1 to 3) for the options you think are acceptable (i.e. you can live with it), where 1 is the most preferred, 2 the next best and so on... You also have a "don't mind" and a "don't want" option.

Rank	Choice
1. MUST be an HTTP(S) hash (#) URI:	The precise definition is:
Don't mind ▾	A WebID is a URI with an http or https scheme, which contains a URI fragment identifier and which uniquely denotes an Agent (Person, Organization, Group, Device, etc.). The URI without the fragment identifier denotes the WebID Profile page.
	Please consider carefully the arguments for this position
2. MUST be an HTTP(S) URI and SHOULD be an HTTP(s) hash (#) URI:	The precise definition is:
1 ▾	A WebID is a URI with an HTTP or HTTPS scheme which uniquely denotes an Agent (Person, Organization, Group, Device, etc.). This URI SHOULD include a fragment identifier.
	Please consider carefully the arguments for this position
3. MUST be an HTTP(S) URI	The precise definition is:
2 ▾	A WebID is a URI with an HTTP or HTTPS scheme which uniquely denotes an Agent (Person, Organization, Group, Device, etc.).
	Please consider carefully the arguments for this position
Rationale:	<div style="border: 1px solid black; height: 65px;"></div>

This questionnaire is open for answers until [23:59, Boston time on 2013-01-03](#). Answers received after that time may not be counted.

The [results of this questionnaire](#) are available only to the participants of the group (and the W3C Team) In addition, answers are sent to the following email address: public-webid@w3.org

Send a copy of these answers to my email address (Henry.Story@bblfish.net) (if this isn't your email address, you can [update your contact information](#)).

You may **completely remove** your response from our records. As this operation is **not reversible**, please confirm your desire to delete your answers by first checking this box:

Delete my answer entirely

[WBS home](#) / [Questionnaires](#) / [Questionnaires for this group](#) / [Results](#) / [Edit questionnaire](#)

See also [who can do what](#) with this questionnaire.

Completed and maintained by [Dominique Hazaël-Massieux \(dom@w3.org\)](#) on an *original design* by [Michael Sperberg-McQueen](#) \$Id: vote.php3,v 1.313 2011/12/14 11:27:41 dom Exp \$. Please send bug reports and request for enhancements to [dom@w3.org](#) with [w3t-sys@w3.org](#) copied (if your mail client supports it, [send mail](#) directly to the right persons)